

Frame anchor with hex head HRD-HF



Base materials

- Concrete (aerated)
- Concrete (cracked)
- Concrete (hollow deck)
- Concrete (uncracked)
- Masonry (grout-filled CMU)
- Masonry (hollow)
- Masonry (hollow CMU)
- Masonry (solid)

Applications

- Fastening metal substructures for ventilated facades
- Typical applications for metal fabricators such as fastening handrails, window bars, railings, balustrades, etc.

Advantages

- Flexible embedment depth (approved at 50 mm and 70 mm embedment depth) - the ideal anchor for a huge range of applications in virtually all base materials
- Pre-assembled for optimum handling and fastening quality


Technical data

Material composition	Steel, hot-dip galvanized (min. 65 µm), Polyamide
Head configuration	Hex head
Anchor size	10 mm
Suitable for cracked concrete with redundant fastenings	Yes

Approvals

ETA | ETA-07/0219 for HRD (ETAG 020-01, Option -)

Approvals and test reports may apply to selected products only. Please refer to the documents for details.



These are abbreviated instructions which may vary by application. Always review/follow the instructions accompanying the product or refer to www.hilti.com/techlib.

Ordering designation	Drill bit diameter	Anchor length	Embedment depth 1	Fastening thickness at embed.1	Screw head diameter	Sales pack quantity	Item number
HRD-HR 10x60	10 mm	60 mm	50 mm	10 mm	18 mm	50 pc	423888 ¹⁾

¹⁾ This is a non-stock item. For detailed lead time information please contact your Hilti representative.

Please visit our website for the latest item numbers and related products.