

Firestop joint spray CFS-SP WB




Applications

- Sealing openings between the top of walls and concrete or metal floors / ceilings
- Sealing building perimeter gaps between floor slabs and exterior curtain wall facades

Advantages

- Water-based, low VOC, contains no halogens
- High degree of elasticity - movement capability of up to 50%
- Excellent sprayability and low slump characteristics
- Fast, efficient sealing of wide, difficult-to-access joints
- Quick and easy installation with airless sprayer can help save time and money
- Both sprayable and brushable



Technical data

Chemical basis	Water-based acrylic dispersion
Base materials	Concrete, Masonry, Gypsum, Steel, Aluminium, Glass
Tested in accordance with	UL 2079, UL 1479, ASTM E84, ASTM E2307, ASTM C1241, ASTM G21, ASTM E90, ASTM E1966, CAN/ULC-S102, CAN/ULC-S115, ASTM E814, EN 1364-4, EN 1366-4, ETA
Movement¹⁾	Up to 50 %
LEED VOC	73 g/l
Can be painted	Yes
Approx. curing time²⁾	3 mm/day
Intumescent	No
Application temperature range	4 - 40 °C
Smoke resistance	Yes

¹⁾ according to HTC 1250

²⁾ at 75°F/24°C, 50% relative humidity



Firestop Systems and Construction Chemicals

Ordering designation	Volume per unit	Sales pack quantity	Item number
CFS-SP WB red	19000 ml	1 pc	430815

Please visit our website for the latest item numbers and related products.